Two Step and Newton- Raphson Algorithms in the Extraction for the Parameters of Solar Cell

Authors Names

- a. Mohammed RASHEED
- b. Suha SHIHAB,
- c. Taha RASHID

Article History

Received on: 3/01/2021

Revised on: 14/01/2021

Accepted on: 18/01/2021

Keywords:

Two step algorithm; Newton's method; numerical solution; iterations; Matlab language

DOI: <https://doi.org/10.29350/jops.2021.26.1.1260>

ABSTRACT

The goal of this work is to find a numerical solution of nonlinear solar cell equation. This equation has been instructed using a single-diode model. The proposed method consists of solving the equation using two iterative methods with the initial value $x_0=1$. Moreover, the Newton's and Two-step methods are used to determine the required the current, the voltage, and the power of the PV cell in the procedure of the present research. Different values of load resistance have introduced with these methods. The obtained results appeared that the proposed method is the most efficient compare with NRM and all the calculations are achieved using Matlab program.

1. Introduction

Scientists began to investigate natural phenomena, whether chemical, physical, engineering, or biological, as various sciences were complicated by the interferences between them and developed terribly. Numerical analysis of all kinds played an important role for explaining these phenomena's in order to obtaining various solutions whether numerical or analytical. Numerical analysis plays a prominent role in solving many physical problems, called communication issues in the science of elasticity, mathematical engineering and mathematics. There have been many ways to

^a Department of Applied Sciences, University of Technology, Baghdad, Iraq,
E-Mail: rasheed.mohammed40@yahoo.com, 10606@uotechnology.edu.iq

^b Department of Applied Sciences, University of Technology, Baghdad, Iraq,
E-Mail: alrawy1978@yahoo.com, 100031@uotechnology.edu.iq

^c Computer and Microelectronics System, Faculty of Engineering, University of Malaysia, Skudai 81310, Johor Bahru, Malaysia,
E-Mail: tsiham95@gmail.com, taha1988@graduate.utm.my

solve these equations, whether analytical or numerical [1, 12, 14, 15, 27, 28, 29, 30, 31, 32, 33, 34, 37, 38, 40, 41, 42, 49, 50, 52 and 53]. Solar cells play an important role in providing clean electricity. Photovoltaic cells, made from semiconductor materials such as silicon, are devices that directly convert solar photons into direct current. Due to the manufacturing techniques and types of materials used in the production of photovoltaic cells, these cells can be classified into three groups [2, 3, 4, 5, 6, 7, 8, 9, 13, 16, 17, 18, 19, 30, 26, 35, 36, 39, 51, 54 and 55]. First group Cells made of silicon crystals. Second group It is divided into four sub-types according to the crystalline structure of the materials involved in its manufacture, as well as the identity and type of materials that include the cells manufactured from the following materials; Amorphous silicon; Polycrystalline silicon; Cadmium Telluride; Indium Copper Alloy. Third group they are the most modern cells, which the world is reliable in obtaining units of highly efficient Solar cells. The cells of this generation are divided into several families: They are the most modern cells, which the world is reliable in obtaining units of highly efficient Solar cells. The cells of this generation are divided into several families, Solar cell nanocrystals; Electrochemical photocells; Polymer solar cells manufactured from polymers; Dye Sensitized solar cells; Solar cells manufactured from molds polymers grafted with inorganic crystals, scientists believe that this type of cells to be manufactured within the fourth generation of solar cells [10, 11, 21, 22, 23, 24 and 25]. For more applications, see [43, 44, 45, 46, 47 and 48]

The aim of this article is to introduce a new iterative algorithm two-step method (2SM) for solving PV cell equation. Two various algorithms are discussed and applied with the comparison between them.

2. Non-Linear Equation Derived from an Electrical Circuit

Figure 1 presents the simple equivalent electronic circuit of a solar cell (neglecting R_s and R_{sh}).

Fig. 1 - Single-diode electrical equivalent circuit of a solar cell.

The final equation of the solar cell current can be extracted according to this equivalent by applying (KCL) Kirchhoff's current law as follows [28 and 50].

$$I = I_{ph} - I_D \quad (1)$$

$$I_D = I_0 \left(e^{\frac{-V_{pv}}{nV_T}} - 1 \right) \quad (2)$$

$$I = I_{ph} - I_0 \left(e^{\frac{-V_{pv}}{mV_T}} - 1 \right) \quad (3)$$

where: I_0 , I_{ph} , I measured in Ampere: reverse saturation current, photocurrent and is reverse saturation current and cell's current respectively. In addition, V_T and V_{pv} the thermic voltage= 26 mV and voltage's cell respectively. The value of the recombination factor of about ($1 < m < 2$), q and k : the electron charge= 1.6×10^{-19} C and Boltzmann constant= 1.38×10^{-23} J/K respectively. Temperature junction is T [29].

$$I_{ph} = I_{source} \quad (4)$$

$$I_D = I_s * \left(e^{\frac{V_D}{nV_T}} - 1 \right) \quad (5)$$

Put Eq. 4 in Eq. 5 yield

$$(I_{source}) - 10^{-12} \left(e^{\frac{-V}{1.2*0.026}} - 1 \right) = \frac{V}{R} \quad (6)$$

where: I_s reverse saturation current= 10^{-12} A. In parallel, $V_D = V_{pv} = V$

The derivative of the Eq. 6 is necessary to find the roots of the V_{pv} numerically.

3. Newton's Technique (NRM)

The following algorithm suggestion for solving Eq. 6 by using NRM

- INPUT initial approximate solution $x_0 = 1$, ε = tolerance, N = maximum number of iterations.
 - Output x_{n+1} = approximate solution
1. Set $x = 0$

2. Step 2: while $i \leq x_0$
3. Step 3: Calculate $x_{n+1} = x_n - \frac{f(x_n)}{\hat{f}(x_n)}$ for $n = 0, 1, 2, \dots$
4. Step 4: If $|x_i - x_{i-1}| < \varepsilon$; so x_{n+1} = approximate solution output and stop.
5. Step 5: put $i = i + 1, n = n + 1$; go to Step 2.
6. Step 6: Output

4. Two Step Iterative Method (2SM)

To compare the different numerical methods of iterations, methods 1 (NRM) has been used against the proposed method 2 (2SM). In addition, Eq. 6. has been solved to demonstrate the performance of the new method, and determine the consistency and stability of results. The results are examined using some iteration.

$$y_n = d_n - \frac{2 \times f(d_n)}{3 \times \hat{f}(d_n)}, n = 0, 1, 2, 3, \dots$$

$$d_{n+1} = d_n - \frac{2 \times f(d_n)}{\hat{f}(d_n) + \hat{\hat{f}}(d_n)}, n = 0, 1, 2, 3, \dots$$

The tolerance and criteria used in the following equations $\varepsilon = 10^{-9}$ and

$$\sigma = |d_{n+1} - d_n| < \varepsilon, |f(d_n)| < \varepsilon$$

5. Results and Discussion

The two numerical methods NRM and 2SM are applied in nonlinear Equation Eq. 6 for PV single diode model and the results obtained are presented in the following Tables for various data of load resistance of the proposed circuit.

Iterations	V_{pv} -NRM	I_{pv} -NRM	P_{pv} -NRM	V_{pv} -2SM	I_{pv} -2SM	P_{pv} -2SM
1	1	1	1	0.962945371	0.962945371	0.927263787
2	0.971416861	0.971416861	0.943650719	0.940361045	0.940361045	0.884278896
3	0.946732606	0.946732606	0.896302627	0.926849876	0.926849876	0.859050692
4	0.929865706	0.929865706	0.864650231	0.922778557	0.922778557	0.851520266
5	0.923247893	0.923247893	0.852386673	0.922426883	0.922426883	0.850871355
6	0.922434	0.922434	0.850884484	0.922423135	0.922423135	0.85086444
7	0.922423136	0.922423136	0.850864443	0.922423135	0.922423135	0.850864439
8	0.922423135	0.922423135	0.850864439			
9	0.922423135	0.922423135	0.850864439			

Table 1 - Comparison of different methods for solving Eq. 6 using NRM and 2SM.

Referring to Table 1 for an initial value $x_0 = 1$, in it very interesting to note the following: at 9th iterations convergence to the root 0.922423135 using NRM while; the proposed method in the Eq. 6 converges to the same approximate root 0.922423135 at 7th iterations. Figure 2 shows the results of the PV parameters obtained by NRM and 2SM.

Fig. 2 – Comparison of PV cell parameters obtained by NRM and 2SM at $R = 1$.

Iterations	V_{pv} -NRM	I_{pv} - NRM	P_{pv} -NRM	V_{pv} -2SM	I_{pv} -2SM	P_{pv} -2SM
1	1	0.5	0.5	0.970250663	0.485125332	0.470693175
2	0.971030472	0.485515236	0.471450089	0.944854325	0.472427163	0.446374848
3	0.945421967	0.472710983	0.446911348	0.926576837	0.463288418	0.429272317
4	0.926834477	0.463417238	0.429511073	0.918396494	0.459198247	0.42172606
5	0.918438746	0.459219373	0.421764865	0.917065915	0.458532958	0.420504947
6	0.917066885	0.458533442	0.420505836	0.917035398	0.458517699	0.420476961
7	0.917035399	0.458517699	0.420476961	0.917035382	0.458517691	0.420476946
8	0.917035382	0.458517691	0.420476946	0.917035382	0.458517691	0.420476946
9	0.917035382	0.458517691	0.420476946			

Table 2 - Comparison of different methods for solving Eq. 6 using NRM and 2SM.

According to Table 2 for an initial value $x_0 = 1$, in it very interesting to note the following: at 9th iterations convergence to the root 0.917035382 using NRM while; the proposed method in the Eq. 6 converges to the same approximate root 0.917035382 at 7th iterations. Figure 3 shows the results of the PV parameters obtained by NRM and 2SM.

Fig. 3 – Comparison of PV cell parameters obtained by NRM and 2SM at $R = 2$.

Iterations	V_{pv} -NRM	I_{pv} -NRM	P_{pv} -NRM	V_{pv} -2SM	I_{pv} -2SM	P_{pv} -2SM
1	1	0.3333333333	0.3333333333	0.969836085	0.323278695	0.313527344
2	0.970643792	0.323547931	0.31404979	0.943460514	0.314486838	0.296705914
3	0.944084232	0.314694744	0.297098346	0.923267523	0.307755841	0.284140973
4	0.923594243	0.307864748	0.284342109	0.912805332	0.304268444	0.277737858
5	0.91287784	0.304292613	0.277781984	0.910498287	0.303499429	0.27633571
6	0.910501262	0.303500421	0.276337516	0.910403527	0.303467842	0.276278194
7	0.910403531	0.303467844	0.276278197	0.910403374	0.303467791	0.276278101
8	0.910403374	0.303467791	0.276278101	0.910403374	0.303467791	0.276278101
9	0.910403374	0.303467791	0.276278101			

Table 3 - Comparison of different methods for solving Eq. 6 using NRM and 2SM.

Based on Table 3 for an initial value $x_0 = 1$, it is very interesting to note the following: at 9th iterations convergence to the root 0.910403374 using NRM while; the proposed method in the Eq. 6 converges to the same approximate root 0.910403374 at 7th iterations. Figure 4 shows the results of the PV parameters obtained by NRM and 2SM.

Fig. 4 – Comparison of PV cell parameters obtained by NRM and 2SM at $R = 3$.

Iterations	V_{pv} -NRM	I_{pv} -NRM	P_{pv} -NRM	V_{pv} -2SM	I_{pv} -2SM	P_{pv} -2SM
1	1	0.25	0.25	0.598809171	0.149702293	0.089643106
2	0.970256822	0.242564205	0.235349575	0.816819533	0.204204883	0.166798538
3	0.94271872	0.23567968	0.222179646	0.884826124	0.221206531	0.195729317
4	0.920123009	0.230030752	0.211656588	0.900161102	0.225040276	0.202572502
5	0.906346494	0.226586624	0.205365992	0.901713938	0.225428485	0.203272007
6	0.902077706	0.225519427	0.203436047	0.901740591	0.225435148	0.203284023
7	0.901742503	0.225435626	0.203284885	0.901740602	0.22543515	0.203284028
8	0.901740602	0.225435151	0.203284028			
9	0.901740602	0.22543515	0.203284028			

Table 4 - Comparison of different methods for solving Eq. 6 using NRM and 2SM.

As a results on Table 4 for an initial value $x_0 = 1$, in it very interesting to note the following: at 9th iterations convergence to the root 0.901740602 using NRM while; the proposed method in the Eq. 6 converges to the same approximate root 0.901740602 at 7th iterations. Figure 5 shows the results of the PV parameters obtained by NRM and 2SM.

Fig. 5 – Comparison of PV cell parameters obtained by NRM and 2SM at R = 4.

Iterations	V_{pv} -NRM	I_{pv} -NRM	P_{pv} -NRM	V_{pv} -2SM	I_{pv} -2SM	P_{pv} -2SM
1	1	0.2	0.2	0.960466918	0.192093384	0.18449934
2	0.96986956	0.193973912	0.188129393	0.932816856	0.186563371	0.174029457
3	0.941324731	0.188264946	0.17721845	0.909783325	0.181956665	0.16554114
4	0.916395843	0.183279169	0.167956268	0.895021368	0.179004274	0.16021265
5	0.898535645	0.179707129	0.161473261	0.889732889	0.177946578	0.158324923
6	0.890477009	0.178095402	0.158589861	0.889104432	0.177820886	0.158101338
7	0.889125763	0.177825153	0.158108925	0.889092721	0.177818544	0.158097173
8	0.889092734	0.177818547	0.158097178	0.889092715	0.177818543	0.158097171
9	0.889092715	0.177818543	0.158097171	0.889092715	0.177818543	0.158097171
10	0.889092715	0.177818543	0.158097171			

Table 4 - Comparison of different methods for solving Eq. 6 using NRM and 2SM.

For an initial value $x_0 = 1$, in it very interesting to note the following: at 10th iterations convergence to the root 0.901740602 using NRM while; the proposed method in the Eq. 6 converges to the same approximate root 0.901740602 at 9th iterations as shown in Table 5. Figure 6 shows the results of the PV parameters obtained by NRM and 2SM.

Fig. 6 – Comparison of PV cell parameters obtained by NRM and 2SM at $R = 5$.

According to the Tables 1, 2, 3, 4 and 5, it is famous that the best approximation to the exact root is often nearer to the initial value, so the results acquired by the proposed method are nearer to the initial approximation $x_0 = 1$, therefore these two methods works better with this type of model (PV – single diode model – nonlinear equation). In addition, the minimum numbers of iterations are appeared by the proposed method 2SM.

6. CONCLUSION

Two-step and Newton's methods were applied to find the numerical solution of the non-linear equation of a solar cell. The methods are tested by taking different values of the load resistance and good results were achieved. The process of computation in these methods is simple because the approximate results were obtained easily by a few computations with the aid of Matlab. Therefore, this approach is considerably powerful. In the proposed method the good results depend on the selecting of the initial value of x_0 are obtained.

REFERENCES

- [1] A. A. Abdulrahman, M. RASHEED and S. SHIHAB, "The Analytic of Image Processing Smoothing Spaces Using Wavelet", In *Journal of Physics: Conference Series*. IOP Publishing, (2021), in press.
- [2] A. AUKŠTUOLIS, M. Girtan, G. A. Mousdis, R. Mallet, M. Socol, and M. Rasheed, "A. Stanculescu, Measurement of charge carrier mobility in perovskite nanowire films by photo-CELIV

- method", *Proceedings of the Romanian Academy Series a-Mathematics Physics Technical Sciences Information Science*, vol. 18 (1), (2017), pp. 34-41.
- [3] D. Bouras, A. Mecif, R. Barillé, A. Harabi, M. Rasheed, A. Mahdjoub, and M. Zaabat, "Cu: ZnO deposited on porous ceramic substrates by a simple thermal method for photocatalytic application", *Ceramics International*, vol. 44 (17), (2018), pp. 21546-21555.
- [4] E. Kadri, K. Dhahri, A. Zaafouri, M. Krichen, M. Rasheed, K. Khirouni, and R. Barillé, "AC conductivity and dielectric behavior of a-Si:H/c-Si_{1-y}Ge_y/p-Si thin films synthesized by molecular beam epitaxial method", *Journal of Alloys and Compounds*, vol. 705, (2017), pp. 708-713.
- [5] E. Kadri, M. Krichen, R. Mohammed, A. Zouari, and K. Khirouni, "Electrical transport mechanisms in amorphous silicon/crystalline silicon germanium heterojunction solar cell: impact of passivation layer in conversion efficiency", *Optical and Quantum Electronics*, vol. 48 (12), (2016), pp. 1-15.
- [6] E. Kadri, O. Messaoudi, M. Krichen, K. Dhahri, M. Rasheed, E. Dhahri, A. Zouari, K. Khirouni, and R. Barillé, "Optical and electrical properties of SiGe/Si solar cell heterostructures: Ellipsometric study", *Journal of Alloys and Compounds*, vol. 721, (2017), pp. 779-783.
- [7] F. Dkhilalli, S. M. Borchani, M. Rasheed, R. Barille, K. Guidara, and M. Megdiche, "Structural, dielectric, and optical properties of the zinc tungstate ZnWO₄ compound", *Journal of Materials Science: Materials in Electronics*, vol. 29 (8), (2018), pp. 6297-6307.
- [8] F. Dkhilalli, S. M. Borchani, M. Rasheed, R. Barille, S. Shihab, K. Guidara, and M. Megdiche, "Characterizations and morphology of sodium tungstate particles", *Royal Society open science*, vol. 5 (8), (2018), pp. 1-12.
- [9] F. Dkhilalli, S. Megdiche, K. Guidara, M. Rasheed, R. Barillé, and M. Megdiche, "AC conductivity evolution in bulk and grain boundary response of sodium tungstate Na₂WO₄", *Ionics*, vol. 24 (1), (2018), pp. 169-180.
- [10] F. S. Tahir, and M. S. Rasheed, "Decline in the Performance of Silicon Solar Cell Parameters with the Ambient Temperature in Baghdad", *Journal of the College of Basic Education*, vol. 18 (75), (2012), pp. 95-111.
- [11] F. S. Tahir, M. S. Rasheed, and I. A. Hameed, "Analysis the Performance of Silicon Solar Cell Parameters with the Ambient Temperature using Fuzzy Logic", *Journal of the College of Basic Education*, vol. 18 (75), (2012), pp. 173-183.
- [12] R. Jalal, S. Shihab, M. A. Sarhan, and M. Rasheed. "Spectral Numerical Algorithm for Solving Optimal Control Using Boubaker-Turki Operational Matrices", In *Journal of Physics: Conference Series*, vol. 1660, no. 1, p. 012090. IOP Publishing, (2020).
- [13] K. Guergouria A. Boumezoued, R. Barille, D. Rechemc, M. Rasheed, and M. Zaabata, "ZnO nanopowders doped with bismuth oxide, from synthesis to electrical application", *Journal of Alloys and Compounds*, vol. 791, (2019), pp. 550-558.
- [14] M. A. Sarhan, "Effect of Silicon Solar Cell Physical Factors on Maximum Conversion Efficiency Theoretically and Experimentally", *Insight-Electronic*, vol. 1 (1), (2019), pp. 24-30.
- [15] M. A. Sarhan, S. Shihab, B. E. Kashem and M. Rasheed, "New Exact Operational Shifted Pell Matrices and Their Application in Astrophysics", In *Journal of Physics: Conference Series*. IOP Publishing, (2021), in press.
- [16] M. Ennefati, B. Louati, K. Guidara, M. Rasheed, and R. Barillé, "Crystal structure characterization and AC electrical conduction behavior of sodium cadmium orthophosphate", *Journal of Materials Science: Materials in Electronics*, vol. 29 (1), (2018), pp. 171-179.

- [17] M. Enneffati, M. Rasheed, B. Louati, K. Guidara, and R. Barillé, "Morphology, UV-visible and ellipsometric studies of sodium lithium orthovanadate", *Optical and Quantum Electronics*, vol. 51 (9), (2019), vol. 299.
- [18] M. Enneffati, M. Rasheed, B. Louatia, K. Guidaraa, S. Shihab, and R. Barillé, "Investigation of structural, morphology, optical properties and electrical transport conduction of $\text{Li}_{0.25}\text{Na}_{0.75}\text{CdVO}_4$ compound", In *Journal of Physics: Conference Series*. IOP Publishing, (2021), in press.
- [19] M. M. Abbas and M. Rasheed, "Solid State Reaction Synthesis and Characterization of Cu doped TiO_2 Nanomaterials", In *Journal of Physics: Conference Series*, IOP Publishing, (2021), in press.
- [20] M. M. Abbas and M. RASHEED, "Investigation of structural, Mechanical, Thermal and Optical Properties of Cu Doped TiO_2 ", *Iraqi Journal of Physics (IJP)*, (2020), in press.
- [21] M. RASHEED, "Investigation of Solar Cell Factors using Fuzzy Set Technique", *Insight-Electronic*, vol. 1 (1), (2019), pp. 17-23.
- [22] M. RASHEED, "Linear Programming for Solving Solar Cell Parameters", *Insight-Electronic*, vol. 1 (1), (2019), pp. 10-16.
- [23] M. Rasheed, and M. A. Sarhan, "Characteristics of Solar Cell Outdoor Measurements Using Fuzzy Logic Method", *Insight-Mathematics*, vol. 1 (1), (2019), pp. 1-8.
- [24] M. RASHEED, and M. A. Sarhan, "Measuring the Solar Cell Parameters Using Fuzzy Set Technique", *Insight-Electronic*, vol. 1 (1), (2019), pp. 1-9.
- [25] M. RASHEED, and M. A. Sarhan, "Solve and Implement the main Equations of Photovoltaic Cell Parameters Using Visual Studio Program", *Insight-Mathematics*, vol. 1 (1), (2019), pp. 17-25.
- [26] M. Rasheed, and R. Barillé, "Room temperature deposition of ZnO and Al: ZnO ultrathin films on glass and PET substrates by DC sputtering technique", *Optical and Quantum Electronics*, vol. 49 (5), (2017), pp. 1-14.
- [27] M. RASHEED, and S. SHIHAB, "Analytical Modeling of Solar Cells", *Insight Electronics*, vol. 1 (2), (2019), pp. 1-9.
- [28] M. RASHEED, and S. SHIHAB, "Modifications to Accelerate the Iterative Algorithm for the Single Diode Model of PV Model", *Iraqi Journal of Physics (IJP)*, vol. 18 (47), (2020), pp. 33-43.
- [29] M. Rasheed, and S. Shihab, "Numerical Techniques for Solving Parameters of Solar Cell", *Applied Physics*, vol. 3 (1), (2020), pp. 16-27.
- [30] M. RASHEED, and S. SHIHAB, "Parameters Estimation for Mathematical Model of Solar Cell", *Electronics Science Technology and Application*, vol. 6, (1), (2019), pp. 20-28.
- [31] M. Rasheed, O. Alabdali and S. Shihab, "A New Technique for Solar Cell Parameters Estimation of The Single-Diode Model", In *Journal of Physics: Conference Series*. IOP Publishing, (2021), in press.
- [32] M. Rasheed, O. Y. Mohammed, S. Shihab, and Aqeel Al-Adili, "A comparative Analysis of PV Cell Mathematical Model", In *Journal of Physics: Conference Series*. IOP Publishing, (2021), in press.
- [33] M. Rasheed, O. Y. Mohammed, S. Shihab, and Aqeel Al-Adili, "Explicit Numerical Model of Solar Cells to Determine Current and Voltage", In *Journal of Physics: Conference Series*. IOP Publishing, (2021), in press.

-
- [34] M. Rasheed, O. Y. Mohammed, S. Shihab, and Aqeel Al-Adili, "Parameters Estimation of Photovoltaic Model Using Nonlinear Algorithms", In *Journal of Physics: Conference Series*. IOP Publishing, (2021), in press.
- [35] M. Rasheed, and R. Barillé, "Comparison the optical properties for Bi_2O_3 and NiO ultrathin films deposited on different substrates by DC sputtering technique for transparent electronics", *Journal of Alloys and Compounds*, vol. 728, (2017), pp. 1186-1198.
- [36] M. Rasheed, and Régis Barillé, "Optical constants of DC sputtering derived ITO , TiO_2 and TiO_2 : Nb thin films characterized by spectrophotometry and spectroscopic ellipsometry for optoelectronic devices", *Journal of Non-Crystalline Solids*, vol. 476, (2017), pp. 1-14.
- [37] M. RASHEED, S. SHIHAB and T. RASHID, "Parameters Determination of PV Cell Using Computation Methods", *Journal of Al-Qadisiyah for Computer Science and Mathematics*, (2021), in press.
- [38] M. Rasheed, S. Shihab, O. Alabdali and H. H. Hussein, "Parameters Extraction of a Single-Diode Model of Photovoltaic Cell Using False Position Iterative Method", In *Journal of Physics: Conference Series*. IOP Publishing, (2021), in press.
- [39] M. RASHEED, S. SHIHAB, and O. W. Sabah, "An investigation of the Structural, Electrical and Optical Properties of Graphene-Oxide Thin Films Using Different Solvents", In *Journal of Physics: Conference Series*. IOP Publishing, (2021), in press.
- [40] M. S. Rasheed and S. Shihab, "Modelling and Parameter Extraction of PV Cell Using Single-Diode Model". *Advanced Energy Conversion Materials*, 1 (2), (2020), pp. 96-104. Available from: <http://ojs.wiserpub.com/index.php/AECM/article/view/550>.
- [41] M. S. Rasheed, "Acceleration of Predictor Corrector Halley Method in Astrophysics Application", *International Journal of Emerging Technologies in Computational and Applied Sciences*, vol. 1 (2), (2012), pp. 91-94.
- [42] M. S. Rasheed, "An Improved Algorithm For The Solution of Kepler's Equation For An Elliptical Orbit", *Engineering & Technology Journal*, vol. 28 (7), (2010), pp. 1316-1320.
- [43] M. S. Rasheed, "Approximate Solutions of Barker Equation in Parabolic Orbits", *Engineering & Technology Journal*, vol. 28 (3), (2010), pp. 492-499.
- [44] M. S. Rasheed, "Comparison of Starting Values for Implicit Iterative Solutions to Hyperbolic Orbits Equation", *International Journal of Software and Web Sciences (IJSWS)*, vol. 1 (2), (2013), pp. 65-71.
- [45] M. S. Rasheed, "Fast Procedure for Solving Two-Body Problem in Celestial Mechanic", *International Journal of Engineering, Business and Enterprise Applications*, vol. 1 (2), (2012), pp. 60-63.
- [46] M. S. Rasheed, "Modification of Three Order Methods for Solving Satellite Orbital Equation in Elliptical Motion", *Journal of university of Anbar for Pure science*, vol. 14 (1), (2020), pp. 33-37.
- [47] M. S. Rasheed, "On Solving Hyperbolic Trajectory Using New Predictor-Corrector Quadrature Algorithms", *Baghdad Science Journal*, vol. 11 (1), (2014), pp. 186-192.
- [48] M. S. Rasheed, "Solve the Position to Time Equation for an Object Travelling on a Parabolic Orbit in Celestial Mechanics", *DIYALA JOURNAL FOR PURE SCIENCES*, vol. 9 (4), (2013), pp. 31-38.
- [49] M. S. Rasheed, and S. Shihab, "Analysis of Mathematical Modeling of PV Cell with Numerical Algorithm". *Advanced Energy Conversion Materials*, vol. 1 (2), (2020), pp. 70-79. Available from: <http://ojs.wiserpub.com/index.php/AECM/article/view/328>.

- [50] M. RASHEED, S. SHIHAB, T. RASHID and T. D. Ounis, "Determination of PV Model Parameters Using Bisection and Secant Methods", *Journal of Al-Qadisiyah for Computer Science and Mathematics*, (2021), in press.
- [51] N. B. Azaza, S. Elleuch, M. Rasheed, D. Gindre, S. Abid, R. Barille, Y. Abid, and H. Ammar, "3-(p-nitrophenyl) Coumarin derivatives: Synthesis, linear and nonlinear optical properties", *Optical Materials*, vol. 96, (2019), pp. 109328.
- [52] S. Shihab, M. Rasheed, O. Alabdali and A. A. Abdulrahman, "A Novel Predictor-Corrector Hally Technique for Determining The Parameters for Nonlinear Solar Cell Equation", In *Journal of Physics: Conference Series*. IOP Publishing, (2021), in press.
- [53] S. SHIHAB, and M. RASHEED, "Modeling and Simulation of Solar Cell Mathematical Model Parameters Determination Based on Different Methods", *Insight Mathematics*, vol. 1 (1), (2019), pp. 1-16.
- [54] T. Saidani, M. Zaabat, M. S. Aida, R. Barille, M. Rasheed, and Y. Almohamed, "Influence of precursor source on sol-gel deposited ZnO thin films properties", *Journal of Materials Science: Materials in Electronics*, vol. 28 (13), (2017), pp. 9252-9257.
- [55] W. Saidi, N. Hfaïdh, M. Rasheed, M. Girtan, A. Megriche, and M. EL Maaoui, "Effect of B₂O₃ addition on optical and structural properties of TiO₂ as a new blocking layer for multiple dye sensitive solar cell application (DSSC)", *RSC Advances*, vol. 6 (73), (2016), pp. 68819-68826.